BWD ISO & QS Certifications



Facility	Boston Weatherhead and a quality and any any and any	Registrar Number	Product Responsibility
Antwerp, OH performers and description of the Design	Hose End Produ	Dana Corporation Bostol Weatherhead Division 1100 741300 7687ue Vinita, OK 74301 with off-eight databilities boosted at:	Steel Hose Ends
Brentwood, TN condition (Engineering)	are fulfilled. ISO/QS9000	Dana Corporation Boston Weatherhead Division 1621 Service Merchandise Blvd. Brentwoo D 37027-1708 Underwriters Laborations Dec ULL, Metville, NY, USA, Issue Above, ether A5225's quality system and fleeding it in ISO 9001:1994; BEN ISO 9001:1994; ANSI/AS and the Quality System Requirements	Patherhead Division Product Product Designs
Cleveland, TN	ISO9002	U.L. conducte. S. G. sent in accordance with the QS-9000 C. Reconducte S. G. sent in accordance with the QS-9000 C. Reconducte S. S. sent in a secondance with the QS-9000 C. S.	Distribution of multiple by the product of the prod
Columbia City, IN ISO14001	ISO9002 97-956	srown pove. By issuance of this certificate the firm represents the applicable recurrences. This certificate is Frie certificate is Frie certificate in Frie Certific	Trimping Equipment
Hohenwald, TN	US98/1495 This is to ear ISO/QS9000 Quality Man ISO/QS9000 DANA CO ISO14001 Cleveland Description Cleveland Description	S. Joe Brustia Executive Vice Plaident and Chief Operating Officer - International A5216 Roosetorie	Industrial and Hydraulic Hose
Ludlow, MA	The Sec heed is supported by su	TUV 74 300 8803	Teflon Hose and Assembly
Newbern, TN	ISO9001 circularia Servicias ISO14001 Mutacipalis Issue No.: 1, November 1998 Valld through November 2001	UL A57548	Industrial and Hydraulic Hose
Vinita, OK	ISO/QS9000 Sanda S	UL A5225 A6947	Brass Fittings, Brass Hose Ends, and Valves

Conversion Chart

Inches			Inches			Inches			Inches		
Fractions	Decimals	MM	Fractions	Decimals	MM	Fractions	Decimals	MM	Fractions	Decimals	MM
-	.0004	.0100		.6693	17.0000	1-25/32	1.7810	45.2440	-	3.1102	79.0000
-	.0040	.1000	43/64	.6720	17.0660	-	1.8110	46.0000	3-1/8	3.1250	79.3750
-	.0100	.2500	11/16	.6875	17.4630	1-13/16	1.8125	46.0380		3.1496	80.0000
1/64	.0156 .0197	.3970	45/64	.7030 .7087	17.8590 18.0000	1-27/32	1.8440	46.8310	3-5/32	3.1560	80.1690
_	.0197	.5000 .7500	23/32	.7190	18.2560	1-7/8	1.8504 1.8750	47.0000 47.6250	3-3/16	3.1875 3.1890	80.9630 81.0000
1/32	.0233	.7940		.7283	18.5000	1-770	1.8898	48.0000	3-7/32	3.2190	81.7560
-	.0394	1.0000	47/64	.7340	18.6530	1-29/32	1.9062	48.4190	J-7752	3.2283	82.0000
3/64	.0469	1.1910	_	.7480	19.0000	-	1.9291	49.0000	3-1/4	3.2500	82.5500
-	.0590	1.5000	3/4	.7500	19.0500	1-15/16	1.9375	49.2130	_	3.2677	83.0000
1/16	.0620	1.5880	49/64	.7656	19.4470	-	1.9685	50.0000	3-9/32	3.2810	83.3440
5/64	.0781	1.9840	25/32	.7810	19.8440	1-31/32	1.9690	50.0060	-	3.3071	84.0000
-	.0787	2.0000		.7874	20.0000	2	2.0000	50.8000	3-5/16	3.3120	84.1377
3/32	.0940	2.3810	51/64	.7970	20.2410		2.0079	51.0000	3-11/32	3.3440	84.9314
7/64	.0984	2.5000	13/16	.8125	20.6380	2-1/32	2.0313	51.5940	_	3.3464	85.0000
7/64	.1090 .1181	2.7780 3.0000	- 53/64	.8268 .8280	21.0000 21.0340	2-1/16	2.0472 2.0620	52.0000 52.3880	3-3/8	3.3750	85.7250
1/8	.1151	3.1750	27/32	.8440	21.4310	2-1/10	2.0866	53.0000	3-13/32	3.3858 3.4060	86.0000 86.5190
""	.1378	3.5000	55/64	.8590	21.8280	2-3/32	20.9400	53.1810	3-13/32	3.4252	87.0000
9/64	.1410	3.5720	_	.8662	22.0000	2-1/8	2.1250	53.9750	3-7/16	3.4380	87.3130
5/32	.1560	3.9690	7/8	.8750	22.2250		2.1260	54.0000	-	3.4646	88.0000
-	.1575	4.0000	57/64	.8906	22.6220	2-5/32	2.1560	54.7690	3-15/32	3.4690	88.1060
11/64	.1720	4.3660	-	.9055	23.0000	-	2.1650	55.0000	3-1/2	3.5000	88.9000
-	.1770	4.5000	29/32	.9062	23.0190	2-3/16	2.1875	55.5630	-	3.5039	89.0000
3/16	.1875	4.7630	59/64	.9220	23.4160	-	2.2047	56.0000	3-17/32	3.5310	89.6940
-	.1969	5.0000	15/16	.9375	23.8130	2-7/32	2.2190	56.3560		3.5433	90.0000
13/64	.2030	5.1590	- 61/64	.9449	24.0000		2.2440	57.0000	3-9/16	3.5620	90.4877
7/32	.2165 .2190	5.5000 5.5560	31/32	.9530 .9690	24.2090 24.6060	2-1/4 2-9/32	2.2500 2.2810	57.1500 57.9440	- 3-19/32	3.5827 3.5940	91.0000 91.2810
15/64	.2340	5.9530	31/32	.9843	25.0000	2-9/32	2.2835	58.0000	3-19/32	3.6220	92.0000
13/04	.2362	6.0000	63/64	.9844	25.0030	2-5/16	2.3120	58.7380	3-5/8	3.6250	92.0750
1/4	.2500	6.3500	1	1.0000	25.4000		2.3228	59.0000	3-3/0	3.6560	92.8960
-	.2559	6.5000	-	1.0236	26.0000	2-11/32	2.3440	59.5310	_	3.6614	93.0000
17/64	.2656	6.7470	1-1/32	1.0312	26.1940	l –	2.3622	60.0000	3-11/16	3.6875	93.6630
-	.2756	7.0000	1-1/16	1.0620	26.9880	2-3/8	2.3750	60.3250	-	3.7008	94.0000
9/32	.2810	7.1440		1.0630	27.0000	-	2.4016	61.0000	3-23/32	3.7190	94.4560
	.2953	7.5000	1-3/32	1.0940	27.7810	2-13/32	2.4060	61.1190	-	3.7401	95.0000
19/64	.2970	7.5410	-	1.1024	28.0000	2-7/16	2.4380	61.9130	3-3/4	3.7500	92.2500
5/16	.3120	7.9380	1-1/8	1.1250 1.1417	28.5750 29.0000		2.4409	62.0000	-	3.7795	96.0000
21/64	.3150 .3280	8.0000 8.3340	1-5/32	1.1560	29.3690	2-15/32	2.4690 2.4803	62.7060 63.0000	3-25/32	3.7810	96.0440
21/04	.3350	8.5000	1-5/32	1.1811	30.0000	2-1/2	2.5000	63.5000	3-13/16	3.8125 3.8189	96.8380 97.0000
11/32	.3440	8.7310	1-3/16	1.1875	30.1630	2-1/2	2.5197	64.0000	3-26/32	3.8440	97.6310
_	.3543	9.0000	1-7/32	1.2190	30.9560	2-17/32	2.5310	64.2940		3.8583	98.0000
23/64	.3590	9.1280	l –	1.2205	31.0000	_	2.5590	65.0000	3-7/8	3.8750	98.4250
-	.3740	9.5000	1-1/4	1.2500	31.7500	2-9/16	2.5620	65.0880		3.8976	99.0000
3/8	.3750	9.5250	-	1.2598	32.0000	2-19/32	2.5940	65.8810	3-29/32	3.9062	99.2190
25/64	.3910	9.9220	1-9/32	1.2810	32.5440	-	2.5984	66.0000	-	3.9370	100.0000
	.3937	10.0000		1.2992	33.0000	2-5/8	2.6250	66.6750	3-15/16	3.9375	100.0130
13/32	.4060	10.3190	1-5/16	1.3120	33.3380	-	2.6380	67.0000	3-31/32	3.9690	100.8060
27/64	.4130	10.5000	- 1-11/32	1.3386	34.0000	2-21/32	2.6560	67.4690		3.9764	101.0000
27/64 —	.4220 .4331	10.7160 11.0000	1-11/32	1.3440 1.3750	34.1310 34.9250	2-11/16	2.6772 2.6875	68.0000 68.2630	4 4-1/16	4.0000 4.0620	101.6000 103.1880
7/16	.4380	11.1130	1-3/6	1.3779	35.0000	2-11/16	2.7165	69.0000	4-1/16	4.0620 4.1250	103.1880
29/64	.4530	11.5090	1-13/32	1.4060	35.7190	2-23/32	2.7190	69.0560	4-1/0	4.1338	104.7750
15/32	.4690	11.9060	-	1.4173	36.0000	2-3/4	2.7500	69.8500	4-3/16	4.1875	106.3630
-	.4724	12.0000	1-7/16	1.4380	36.5130		2.7559	70.0000	4-1/4	4.2500	107.9500
31/64	.4840	12.3030	-	1.4567	37.0000	2-25/32	2.7810	70.6439	4-5/16	4.3120	109.5380
-	.4920	12.5000	1-15/32	1.4690	37.3060	-	2.7953	71.0000	-	4.3307	110.0000
1/2	.5000	12.7000		1.4961	38.0000	2-13/16	2.8125	71.4376	4-3/8	4.3750	111.1250
	.5118	13.0000	1-1/2	1.5000	38.1000		2.8346	72.0000	4-7/16	4.4380	112.7130
33/64	.5156	13.0970	1-17/32	1.5310	38.8940	2-27/32	2.8440	72.2314	4-1/2	4.5000	114.3000
17/32	.5310	13.4940	1-9/16	1.5354 1.5620	39.0000 39.6880	2 7/9	2.8740	73.0000	4 0/46	4.5275	115.0000
35/64 —	.5470 .5512	13.8910 14.0000	1-9/16	1.5620 1.5748	40.0000	2-7/8 2-29/32	2.8750 2.9062	73.0250 73.8190	4-9/16	4.5620	115.8880 117.4750
9/16	.5630	14.0000	1-19/32	1.5940	40.4810	2-29/32	2.9062	74.0000	4-5/8 4-11/16	4.6250 4.6875	117.4750
9/10	.5710	14.5000	-	1.6142	41.0000	2-15/16	2.9375	74.6130	4-11/16	4.7244	120.0000
37/64	.5790	14.6840	1-5/8	1.6250	41.2750		2.9527	75.0000	4-3/4	4.7500	120.6500
-	.5906	15.0000	-	1.6535	42.0000	2-31/32	2.9690	75.4060	4-13/16	4.8125	122.2380
19/32	.5940	15.0810	1-31/32	1.6562	42.0690	-	2.9921	76.0000	4-7/8	4.8750	123.8250
39/64	.6090	15.4780	1-11/16	1.6875	42.8630	3	3.0000	76.2000	_	4.9212	125.0000
5/8	.6250	15.8750	-	1.6929	43.0000	3-1/32	3.0312	76.9940	4-15/16	4.9375	125.4130
-	.6299	16.0000	1-23/32	1.7190	43.6560	-	3.0315	77.0000	5	5.0000	127.0000
41/64	.6406	16.2720	-	1.7323	44.0000	3-1/16	3.0620	77.7880			
-	.6496	16.5000	1-3/4	1.7500	44.4500		3.0709	78.0000			
21/32	.6560	16.6690	_	1.7717	45.0000	3-3/32	3.0940	78.5810	<u> </u>		

Technical Torque Specifications

JIC 37° and SAE 45° Flare Fittings For Zinc Plated Carbon without Thread Sealant or Lubrication

Size	Fraction	Decimal	Lb. / In.	Lb. / Ft.	Newton Meters	Additonal Turns of Hex-Flats**
- 04	1/4"	0.250	130-150	11-12	15-17	2
- 05	5/16"	0.312	165-195	14-16	19-22	2
- 06	3/8"	0.375	235-265	20-22	27-30	1-1/4
- 08	1/2"	0.500	525-575	44-48	59-65	1
- 10	5/8"	0.625	600-700	50-58	68-79	1
- 12	3/4"	0.750	950-1050	79-88	107-119	1
- 16	1"	1.000	1400-1500	117-125	158-170	1
- 20	1-1/4"	1.250	1900-2100	158-175	215-237	1
- 24	1-1/2"	1.500	2250-2550	188-213	254-288	1
- 32	2"	2.000	3000-3400	250-283	339-384	1

^{**}Additional Turns of Hex-Flats required after finger tightening. THIS IS THE RECOMMEND METHOD OF TIGHTENING BOTH 37° SWIVELS & 45° FLARE FITTINGS.

Straight Thread O-Ring Fittings For Zinc Plated Steel without Sealant or Lubrication

Size	Fraction	Decimal	Lb. / In.	Lb. / Ft.	Newton Meters
- 04	1/4"	0.250	156-180	13-15	18-20
- 05	5/16"	0.312	204-228	17-19	23-26
- 06	3/8"	0.375	264-288	22-24	30-33
- 08	1/2"	0.500	480-516	40-43	54-58
- 10	5/8"	0.625	516-576	43-48	58-65
- 12	3/4"	0.750	816-900	68-75	92-102
- 16	1"	1.000	1344-1476	112-123	152-167
- 20	1-1/4"	1.250	1752-1932	146-161	198-218
- 24	1-1/2"	1.500	1848-2040	154-170	209-231
- 32	2"	2.000	2616-2880	218-240	296-325

For-Seal[®] Fittings For Zinc Plated Steel without Thread Sealant or Lubrication

			For-S Swivel Nu		C Straight Thi	-Ring Boss read O-Ring		
Size	Fraction	Decimal	Lb. / In.	Lb. / Ft.	Newton Meters	Lb. / ln.	Lb Ft.	Newton Meters
- 04	1/4"	0.250	120-144	10-12	14-16	168-192	14-16	19-22
- 06	3/8"	0.375	216-240	18-20	24-27	288-312	24-26	33-35
- 08	1/2"	0.500	384-420	32-35	43-48	600-720	50-60	68-81
- 10	5/8"	0.625	552-600	46-50	62-68	864-960	72-80	98-109
- 12	3/4"	0.750	780-840	65-70	88-95	1500-1620	125-135	170-183
- 16	1"	1.000	1104-1200	92-100	125-136	2400-2640	200-220	271-298
- 20	1-1/4"	1.250	1500-1680	125-140	170-190	2520-3360	210-280	285-380
- 24	1-1/2"	1.500	1800-1980	150-165	203-224	3240-4320	270-360	366-488

Torque Value Conversion Chart										
Lb. / Inch	=	Pound Foot (Lb./Ft.) x 12	Lb. / Foot	=	Pound Inch (Lb./In.) x 0.083					
Lb. / Inch		Newton Meter x 8.850	Lb. / Foot	=	Newton Meter x 0.737					
Newton Meter		Pound Inch (Lb./In.) x 0.113	Newton Meter	=	Pound Foot (Lb./Ft.) x 1.356					

Boston Weatherhead Tech Support 1-800-776-3262

Our "800" service is provided for your benefit and is available from 8:00 AM to 7:00 PM Monday through Friday Eastern time.

The Technical Support Group will assist you with information relative to:

- Part number interchanges
- · Weatherhead part number verification
- · Hose, hose ends, and fitting identification based on application information
- · Identification of tube and pipe fittings based on description and dimensions
- Applications not listed in current catalogs
- · Chemical resistance ratings
- · Dimensions
- · Coll-O-Crimp hose crimper information, troubleshooting, and replacement parts
- Selection of correct Coll-O-Crimp tooling
- · Construction, materials, and properties of hose and fittings
- Weatherhead tools and accessories
- Hose assembly troubleshooting and problem solving
- Referral to a Weatherhead distributor or District Sales Manager

The Technical Support Group *cannot* respond to the following:

- Transfer of calls to another department or the warehouse
- Inventory status
- Backorders
- · Pricing and placing orders
- · Literature orders
- Competitive pricing

We appreciate the opportunity to provide these services to you. Your comments and suggestions are welcome.

NO PRODUCT LISTED IN THIS CATALOG HAS BEEN CERTIFIED FOR AVIATION USE.

This catalog and all information herein supersede all previous Weatherhead catalogs and information material.

A:

abrasion: external damage to a hose assembly caused by its being rubbed on a foreign object; a wearing away by friction.

ABS: Air-Brake Swivel

absorption: regarding hose, the process of taking in fluid. Hose materials are often compared with regard to relative rates and total amounts of absorption as they pertain to specific fluids.

acid resistant: having the ability to withstand the action of identified acids within specified limits of concentration and temperature

adapter, adaptor: 1) fittings of various sizes and materials used to change an end fitting from one type to another type or one size to another. (i.e., a male SAE to male pipe adapter is often attached to a female SAE to create a male end union fitting); 2) the grooved portion of a cam & groove coupling.

adhesion: the strength of bond between cured rubber surfaces or between a cured rubber surface and a non-rubber surface.

adhesive: a material which, when applied, will cause two surfaces to adhere.

ambient/atmospheric conditions: The surrounding conditions, such as temperature, pressure, and corrosion, to which a hose assembly is exposed.

anchor: a restraint applied to eliminate motion and restrain forces

annular: refers to the convolutions on a hose that are a series of complete circles or rings located at right angles to the longitudinal axis of the hose (sometimes referred to as "bellows").

anodize, anodized: an electrolytic process used to deposit protective or cosmetic coatings in a variety of colors on metal, primarily used with aluminum.

ANSI: American National Standards Institute.

Application working pressure: unique to customer's application. See pressure, working.

armor: a protective cover slid over and affixed to a hose assembly; used to prevent over bending or for the purpose of protecting hose from severe external environmental conditions such as hot materials, abrasion or traffic.

assembly: a general term referring to any hose coupled with end fittings of any style attached to one or both ends.

ASTM: American Society for Testing and Materials.

axial movement: compression or elongation along the longitudinal axis.

В

backing: a soft rubber layer between a hose tube and/or cover and carcass to provide adhesion.

barb: the portion of a fitting (coupling) that is inserted into the hose, usually comprised of two or more radial serrations or ridges designed to form a redundant seal between the hose and fitting. barbed and ferrule fitting: a two-piece hose fitting comprised of a barbed insert (nipple), normally with peripheral ridges or backward-slanted barbs, for inserting into a hose and a ferrule, usually crimped or swaged.

Barb-Tite™: a line of low pressure push-on brass hose end fittings that is a Trademark of Dana Corporation.

bend radius: the radius of a bent section of hose measured to the innermost surface of the curved portion.

bend radius, minimum: the smallest radius at which hose or tubing can be used. For Metal Hose: the radius of a bend measured to the hose centerline, as recommended by the manufacturer.

blister: a raised area on the surface or a separation between layers usually creating a void or air-filled space in a vulcanized article.

body wire: normally a round or flat wire helix embedded in the hose wall to increase strength or to resist collapse.

bore: (1) an internal cylindrical passageway, as of a tube, hose or pipe; (2) the internal diameter of a tube, hose, or pipe.

braid: the woven portion of a hose used as reinforcement to increase pressure rating and add hoop strength. Various materials such as polyester, cotton or metal wire are used. A hose may have one or more braids, outside or between layers of hose material.

braided ply: a layer of braided reinforcement.

brand: a mark or symbol identifying or describing a product and/ or manufacturer, that is embossed, inlaid or printed.

brass: a family of copper/zinc alloys.

brazing: a process of joining metals using a non-ferrous filler metal having a melting point that is lower than the "parent metals" to be joined, typically over +800°F.

bronze: an alloy of copper, tin and zinc.

BSPP/BSPT: British Standard Pipe Parallel / British Standard Pipe Tapered. See Fitting/Coupling - Pipe Thread Fittings.

C:

carcass: the fabric, cord and/or metal reinforcing section of a hose as distinguished from the hose tube or cover.

chalking: the formation of a powdery surface condition due to disintegration of surface binder or elastomer by weathering or other destructive environments.

checking: the short, shallow cracks on the surface of a rubber product resulting from damaging action of environmental conditions

chemical compatibility: the relative degree to which a material may contact another without corrosion, degradation or adverse change of properties.

chemical resistance: the ability of a particular polymer, rubber compound, or metal to exhibit minimal physical and/or chemical property changes when in contact with one or more chemicals

for a specified length of time, at specified concentrations, pressure, and temperature.

cold flexibility: relative ease of bending while being exposed to specified low temperature.

collar: 1) the portion of a fitting that is compressed by crimping to seal the hose onto the fitting barbs and create a permanent attachment; also called a ferrule. (With field attachable fittings, the lock and seal are accomplished mechanically by the collar without crimping); 2) a raised portion on the hose shank which functions as a connection for a ferrule or other locking device or functions as a hose stop.

Coll-O-Crimp[®]: a line of hydraulic and pneumatic hose, hose end fittings, and fabrication equipment that is a registered trademark of Dana Corporation.

combustible liquid: a combustible liquid is one having a flash point at or above +100°F (37.8°C).

compound: the mixture of rubber or plastic and other materials, which are combined to give the desired properties when, used in the manufacture of a product.

compression fitting: see fitting/coupling - Compression

conductive: the ability to transfer electrical potential.

configuration: the combination of fittings on a particular assembly.

convoluted: description of hose or innercore having annular or helical ridges formed to enhance flexibility.

core: the inner portion of a hose, usually referring to the material in contact with the medium.

corrosion: the process of material degradation by chemical or electrochemical means.

corrosion resistance: ability of metal components to resist oxida-

corrugated hose: hose with a carcass fluted, radially or helically, to enhance its flexibility or reduce its weight.

coupling: a frequently used alternative term for hose end fitting.

cover: the outer component usually intended to protect the carcass of a product.

CPE: chlorinated polyethylene, a rubber elastomer.

cracking: a sharp break or fissure in the surface, generally caused by strain and environmental conditions.

crimp diameter: the distance across opposite flats after crimping.

crimp/crimping: a hose end fitting attachment method utilizing a number of dies mounted in a radial configuration. The dies close perpendicular to the hose and fitting axis, compressing the collar, ferrule, or sleeve around the hose.

cure: the act of vulcanization. See vulcanization.

cut off factor: the hose length to be subtracted from the overall assembly length that allows for the hose coupling end connection extension beyond the end of the hose.

D:

date code: any combination of numbers, letters, symbols or other methods used by a manufacturer to identify the time of manufacture of a product.

deburn: to remove ragged edges from the inside diameter of a hose end.

design factor: a ratio used to establish the working pressure of the hose, based on the burst strength of the hose.

DOT: Department of Transportation.

DIN: Deutsche Industrie Norme.

duplex assembly: an assembly consisting of two hose assemblies-one inside the other, and connected at the ends; also known as "jacketed assemblies."

durometer: an instrument for measuring the hardness of rubber and plastic compounds.

E:

eccentricity: the condition resulting from the inside and outside diameters not having a common center.

effusion: the escape, usually of gases, through a material. See permeation.

elastic limit: the limiting extent to which a body may be deformed and yet return to its original shape after removal of the deforming force

elastomer: any one of a group of polymeric materials, usually designated thermoset, such as natural rubber, or thermoplastic, which will soften with application of heat.

elongation: the increase in length expressed numerically as a percentage of the initial length.

ERMETO™: a steel fitting product trademarked by Dana Corporation.

endurance test: a service or laboratory test, conducted to product failure, usually under normal use conditions.

EPDM: Ethylene Propylene Diene Monomer; an elastomer.

extrude/extruded/extrusion: forced through the shaping die of an extruder; extrusion may have a solid or hollow cross section.

F:

fabric impression: impression formed on the rubber surface during vulcanization by contact with fabric jacket or wrapper.

fabricator: the producer of hose assemblies.

fatigue: the weakening or deterioration of a material occurring when a repetitious or continuous application of stress causes strain, which could lead to failure.

FDA: United States Food and Drug Administration.

fire sleeve: slip-on or integrally extruded sleeve used to retard the effects of fire in certain applications; most often made with

silicone and/or ceramic fiber.

fitting/coupling: a device attached to the end of the hose to facilitate connection. The following is only a partial list of types of fittings available-

Compression Fitting - a fitting style that seals on a mating tube by compressing an internal ferrule against the tube O.D..

Field Attachable Fitting - a fitting designed to be attached to hose without crimping or swaging. This fitting is not always a reusable type fitting.

Flange Style Fittings - pipe flanges and flanged fitting standards are listed under ANSI B16.5. Flanges are rated for pressure and listed as "American Class 150, 300, 400, 600, 900, 1,500 or 2,500". Pressure-Temperature ratings can be obtained by consulting the ANSI specification or ASME B16.5 (American Society of Mechanical Engineers). Designs vary by neck and face style, or other dimensional changes based on use. Various finishes or grooves may be applied to the face for sealing on a gasket or o-ring. Bolt holes and other dimensions are per the ANSI standard.

Inverted Flare Fitting - a fitting consisting of a male or female nut, trapped on a tube by flaring the end of the tube material to either 37° or 45°.

JIC Fittings - joint Industrial Council (no longer in existence). An engineering group that established an industry standard fitting design incorporating a 37° mating surface, male and female styles. These standards are now governed by SAE.

O-ring Fittings - a fitting that seals by means of an elastomeric ring of a specified material.

Pipe Thread Fittings -

NPT - National Pipe Taper. Pipe thread per ANSI B1.20.1

NPTF - National Pipe Tapered for Fuels. (Same as above except dry-seal per ANSI B1.20.3)

NPSH - National Pipe Straight Hose per ANSI B1.20.7

NPSM - National Pipe Straight Mechanical. Straight thread per ANSI B1.20.1

NPSL - National Pipe Straight Loosefit per ANSI B1.20.1

BSPP, BSPT - British Standard Pipe Parallel, British Standard Pipe Taper. BS21

Quick Connect Fitting - a fitting designed to quickly connect and disconnect. These fittings come in many styles and types.

Split Flange Fitting - a fitting consisting of a flange retainer and a flange of two halves. This design allows the flanges to be installed after the retainer has been attached to the hose, making the flange reusable. SAE Code 61 and 62.

Tube Fitting - a hose fitting of which the mating end conforms to a tube diameter. The mate or male end of a compression fitting.

flammable gases/liquid/media: a flammable gas, including liquefied gas, is one having a closed cup flash point below +100°F (+37.8°C) and a vapor pressure greater than 25 psi. (174.2 KPa).

flex cracking: a surface cracking induced by repeated bending and straightening.

flow rate: a volume of media being conveyed in a given time period

fluid: a gas or liquid medium.

fluorocarbon: an organic compound containing fluorine directly bonded to carbon. The ability of the carbon atom to form a large variety of structural chains gives rise to many fluorocarbons and fluorocarbon derivatives.

FOR-SEAL™: a product name for a hose end configuration using an o-ring sealing method, trademarked by Dana Corporation.

G:

GPM: gallons per minute.

H:

heat resistance: the property or ability to resist the deteriorating effects of elevated temperatures.

helix: a shape formed by spiraling a wire or other reinforcement around the cylindrical body of a hose; typically used in suction hose

hose: a flexible conduit consisting of a tube, reinforcement, and usually an outer cover.

hydrostatic testing: the use of liquid pressure to test a hose or hose assembly for leakage, twisting, and/or hose change-in-length.

Hytrel[®]: a DuPont registered trademark.

Ŀ

I.D.: the abbreviation for inside diameter.

identification yarn: a yarn of single or multiple colors, usually embedded in the hose wall, used to identify the manufacturer.

impression: a design formed during vulcanization in the surface of a hose by a method of transfer, such as fabric impression or molded impression.

impulse: an application of force in a manner to produce sudden strain or motion, such as hydraulic pressure applied in a hose.

innertube: the innermost layer of a hose; the hose material in contact with the medium.

insert: optional term for nipple. See nipple.

interlocking clamp: a clamp which engages the fitting in a manner which prevents the clamp from sliding off the fitting, typically

M I S C

Alpha/Numeric

a bolt or U-bolt style with interlocking fingers which engage an interlock ring on the fitting.

interlocking ferrule: a ferrule, which physically attaches to the fitting preventing the ferrule from sliding off the fitting.

ISO: International Organization for Standardization.

J:

jacket: a seamless tubular braided or woven ply generally on the outside of a hose.

JIC: see fitting/coupling-JIC.

K:

kinking: a temporary or permanent distortion of the hose induced by bending beyond the minimum bend radius.

L:

layline: the line of printed information that runs parallel on the side of a manufactured hose giving details such as part number, PSI rating, hose size and manufacturing data.

layer: a single thickness of rubber or fabric between adjacent parts.

loop installation: the assembly is installed in a loop or "U" shape, and is most often used when frequent and/or large amounts of motion are involved

LPG, LP Gas: the abbreviation for liquefied petroleum gas.

M:

MAWP: see pressure, maximum allowable working.

manufacturer's identification: a code symbol used on or in some hose to indicate the manufacturer.

media, medium: the substance(s) being conveyed through a system.

N:

NAHAD: the abbreviation for the National Association of Hose & Accessories Distributors.

Neoprene®: a registered trademark of DuPont.

nipple: the internal member or portion of a hose fitting.

nitrile rubber (NB/Buna-N): a family of acrylonitrile elastomers used extensively for industrial hose.

nominal: a size indicator for reference only.

nomograph: a chart used to compare hose size to flow rate to recommended velocity.

non-conductive: the inability to transfer an electrical charge.

NPT/NPTF: abbreviation for national pipe threads. See fitting/coupling - Pipe Thread Fittings.

nylon: a family of polyamide materials.

O.

OAL: see overall length

O.D.: the abbreviation for outside diameter.

OE/OEM: original equipment manufacturer.

oil resistance: the ability of the materials to withstand exposure to oil

oil swell: the change in volume of a rubber article resulting from contact with oil.

operating conditions: the pressure, temperature, motion, and environment to which a hose assembly is subjected.

o-ring fitting: see fitting/coupling, O-Ring.

overall length (OAL): the total length of a hose assembly, which consists of the free hose length plus the length of the coupling(s).

oxidation: the reaction of oxygen on a material, usually evidenced by a change in the appearance or feel of the surface or by a change in physical properties.

ozone cracking: the surface cracks, checks or crazing caused by exposure to an atmosphere containing ozone.

ozone resistance: the ability to withstand the deteriorating effects of ozone (generally cracking).

P:

permanent fitting: the type of fitting which, once installed, may not be removed for re-use.

permeation: the process of migration of a substance into and through another, usually the movement of a gas into and through a hose material; the rate of permeation is specific to the substance, temperature, pressure and the material being permeated.

pin pricked: perforations through the cover of a hose to vent permeating gases.

pitch: 1) the distance from one point on a helix to the corresponding point on the next turn of the helix, measured parallel to the axis; 2) the distance between the two peaks of adjacent corrugation or convolution.

plating: a material, usually metal, applied to another metal by electroplating, for the purpose of reducing corrosion; typically a more noble metal such a zinc is applied to steel.

ply: an individual layer in hose construction.

polymer: a macromolecular material formed by the chemical combination of monomers, having either the same or different chemical compositions.

pressure: force ÷ unit area. For purposes of this document, refers to PSIG (pounds per square inch gauge).

pressure drop: the measure of pressure reduction or loss over a specific length of hose.

pressure, burst: the pressure at which rupture occurs.

pressure, maximum allowable working: the maximum pressure at which a hose or hose assembly is designed to be used.

pressure, working: the maximum pressure to which a hose will be subjected, including the momentary surges in pressure, which can occur during service. Abbreviated as WP.

psi (PSI): pounds per square inch.

PTFE: polytetrafluoroethylene, a high molecular weight fluoroplastic polymer with carbon atoms shielded by fluorine atoms having very strong inter atomic bonds, giving it chemical inertness

Push > Connect™: (Push > Connect™ Metric, Push > Connect™ Flow Controls, Push > Connect™ Plus) A Reusable, easy to assemble fitting recommended on compressed air, lubrication, and pneumatic instrumentation applications. Use with approved tubing material.

PVC: polyvinyl chloride. A low cost thermoplastic material typically used in the manufacture of industrial hoses. The operating temperature range is -500°F to +1750°F (-295.5°C to +954.4°C).

0

Quick > Connect™: A reusable easy to assemble air brake fitting used on NT100 series tubing. This fitting meets D.O.T. performance requirements.

R٠

reinforcement: the strengthening members, consisting of either fabric, cord, and/or metal, of a hose. See ply.

reusable fitting/coupling: see fitting/coupling, Field Attachable Fittings.

RhinoHide[®]: a product's name for an abrasion resistant covered hydraulic hose that is a registered trademark of Dana Corporation.

RMA: The Rubber Manufacturers Association, Inc.

S

SAE: Society of Automotive Engineers.

shank: that portion of a fitting, which is inserted into the bore of a hose.

skive: the removal of a short length of cover and/or tube to permit the attachment of a fitting directly over the hose reinforcement.

sleeve: a metal cylinder, which is not physically attached to the fitting, for the purpose of forcing the hose into the serrations of the fitting.

smooth bore: a term used to describe the type of innercore in a hose.

specification: a document setting forth pertinent details of a product

spiral: a method of applying reinforcement in which there is not interlacing between individual strands of the reinforcement.

spring guard: a helically wound component applied internally or externally to a hose assembly, used for strain relief, abrasion resistance, collapse resistance.

standard: a document, or an object for physical comparison, for defining product characteristics, products, or processes, prepared by a consensus of a properly constituted group of those substantially affected and having the qualifications to prepare the standard for use.

static wire: wire incorporated in a hose to conduct static electricity.

stem: see nipple.

surge (spike): a rapid and transient rise in pressure.

swelling: an increase in volume or linear dimension of a specimen immersed in liquid or exposed to a vapor.

Т

Teflon®: a registered trademark of E.I. DuPont. See PTFE, FEP and PFA.

tube: the innermost continuous all-rubber or plastic element of a hose.

tube fitting: see fitting/coupling-Tube.

tubing: a non-reinforced, homogeneous conduit, generally of circular cross-section.

V:

vacuum resistance: the measure of a hoses ability to resist negative gauge pressure.

vibration: amplitude motion occurring at a given frequency.

viscosity: the resistance of a material to flow.

vulcanization: a process during which a rubber compound, through a change in its chemical structure, improves or extends elastic properties over a greater range of temperature.

W:

weathering: the surface deterioration of a hose cover during outdoor exposure, as shown by checking, cracking, crazing and chalking.

wire reinforced: a hose containing wires to give added strength, increased dimensional stability; crush resistance. See reinforcement.

working temperature: the temperature range of the application, may include the temperature of the fluid conveyed or the environmental conditions the assembly is exposed to in use.

WP: the abbreviation for working pressure.

The preceding Glossary of Terms, as utilized in the hose industry, includes some definitions from The Hose Handbook, published by the Rubber Manufacturers Association.

Index

A55SCUx76 I	BA-56X240	l C5755x180
A555111	BA-84	C5880x17
		C5924x
A555P 113	BA-84X 239	
A555S111	BF-40 236	C9200125
A556P 113	BF-40X 235, 235, 236, 237, 242	C9240125
A557MCUx76	BF-41236	C-5X248
	BF-42237	I
A557SCUx76		C-15X231, 232
A655 111	BF-43 237	C-63X231, 232, 234, 241, 248
A655S111	BL-456247	C-632X232, 232, 233
A660111	BL-456X 244, 246	CA-10X245
A664 119	C3059x 140	CA-130245
A690 111	C3069x142	CA-230245
A690P 113	C3109x141	CA-631234
A690S111	C3159x140	CA-631CO234
		CA-631CU232
A694 119	C3169x 140	CA-632232, 233
A694S 119	C3179x 140	CA-632CO233
A735 111	C3209x141	CB-63X231, 232, 234
A6690111	C3239x142, 186	CD-15231, 232
A6690S111	C3249x 142, 184	CD-15D23
A6754 119	C3269x141, 184	CL-16-1230, 234
A6754S 119	C3309x142	CL-16-2230, 243
A6755111		
	C3359x143	CL-16-391, 230, 24
A6755S111	C3409x144	CL-434230, 249
A6759 119	C3459x 145, 192	CL-490 37, 42, 48, 104, 230, 233, 234
A6760111	C3469x 145, 193	CL-491
A6760P 113	C3509x144	CL-492230
A6760S111	C3529x 146	CL-493230
A6763111	C3559x143	CL-494230
A6763S111	C3609x146	CL-496
A6764 119	C3709x146	CL-497230, 24
A6764S 119	C3759x147	CL-49860, 230
A6765111	C3959x147	CL-49965, 230, 238
A6765S111	C5015x	CL-50054, 230
		,_,_,
A6769 119	C5105x 166	CL-501230
A6769S 119	C5115x 166	CL-502230, 248
A6770 111	C5125x166	CL-50383. 230. 242
A6774 119	C5129x167	DC-121238
A6775 111	C5165x 166, 184	FA-100247
A6775S111	C5165x-MM 166, 213, 248	FA-100-CO24
A6779 119	C5205x 169	FC-16X231, 234, 238, 241, 242, 243
A6779S 119	C5216x	FC-161234
A6793 118	C5229x 167	FH-15X231, 243, 247, 249
A6845 111	C5255x 169	FL-310249
A6845S111	C5256x172	FL-310X249
A6855111	C5275x 169	FS-100230
A6855S111	C5305x168	FS-200 164, 230
A6860 111	C5306x 168	FS-300 208, 209, 230
A6860P 113	C5314x184	FS-500230
A6860S111	C5315x170, 187	FS-501230. 246
AB-8245	C5316x170, 187	FS-800
AB-8L 245	C5325x 168	FS-900 91, 230
AB-8X 245	C5355x172	FS-1000 79, 230
AB-9 245	C5356x173	FS-1600 195, 230
AB-9L 245	C5365x	FS-2000 139, 230
	,	
AB-9X 245	C5405x 175	FS-2100 60, 230
AB-28 243	C5425x 176	FS-2400 154, 230
AB-45 243	C5455x177	FS-2500249
AB-140 241	C5505x174	FS-330083, 230
		1
AB-1400 241	C5506x177	FS-SA-2244
B735 111	C5515x 178, 190	H05703246
BA-24 240	C5525x176	H05704246, 249
BA-24X240	C5605x181	H05705246, 249
BA-28 240	C5655x182	H05706246, 249
BA-28X240	C5705x 179	H06904247
		1 1100000
BA-38240 I	C5706x180	HU69U6/4
BA-38240 BA-38X 240	C5706x	H06906247
BA-38X240	C5707x 182	H06908247
BA-38X 240 BA-48 240	C5707x 182 C5715x 183, 193	H06908247 H06910247
BA-38X240	C5707x 182	H0690824 H0691024 H1010424
BA-38X 240 BA-48 240	C5707x 182 C5715x 183, 193	H06908247 H06910247

H10106246	PT2400634	400 040
H1U1U6240	P124006	SJ312 128, 240
H16606247	PT2400834	SJ320 128. 240
		_ = = = = = = = = = = = = = = = = = = =
H16608247	PT2401034	SJ330128. 240
H33806247	PT2401234	SJ340 128, 240
HA-574 246	PT2401634	SJ351 128, 240
		33331120, 240
HC-574X246	QC-18242	SJ360
HD-1X247	QC-18X242	SS-85235
M7629x214, 248	QC-180242	SS-86 235
M7C20v 244	QC-1800242	SS-87 235
M7630x214	QC-1800242	33-8 /235
M9600x217, 248	RG-24 223	SS-88 236
M9700x214, 248	S306 128, 223, 239	T-100227
M9800x217, 248	S308 128, 239	T-104 227
		T 405
M41157x 124	S310 128	T-105 227
MA-100248	S312 128, 239, 240	T-106227
MA-200 249	\$320 128, 239, 240	T-107227
MB5315x217, 248	\$330	T-108227
MDEE45 040 040		T 405D
MB5515x218, 248	\$340 128, 239, 240	T-125B 226
MB7629x218	S351 128, 239, 240	T-135226
	, ,	
MB7630x218	S360 128, 239, 240	T-135B 226
	, ,	
MC3069x216	S372 128, 239	T-138 226
	-,	
MC3159x215	\$408 128	T-138B 226
MC3309x215	S412 128, 239, 240	T-139225
	-,, -	
MC5019x171, 212	\$420	T-139P225
111, 212		
MC5205x216, 248	S430 128, 239, 240	T-140225
MC5206x212, 248	S440 128, 239, 240	T-141225
MC5207x212, 248	S451	T-142225
	-,, -	1
MC5208x212, 248	S460	T-143225
MC5315x213, 248	S512 128, 239, 240	T-144225
MC5405x218, 248	\$520 128, 239, 240	T-145 225
MC5515x214, 248	\$530	T-146225
MH7105x 211, 248, 249	\$540 128, 239, 240	T-147225
100X		
ML7105 x211, 248, 249	\$551 128, 239, 240	T-148225
		T 440
MTP1600435	\$560	T-149 225
MTP1600535	S612	T-150225. 228
	3012 120, 240	1-130223, 220
MTP1600635	\$620	T-151225
MTP1600835	S630 128. 240	T-152225
MTP1601035	0040	T 450D
WITP1601035	\$640 128, 240	T-152P 225
MTP1601235	S651 128, 240	T-191 226, 242
	,	1
NT1000233. 244	\$660	T-191B226
NT1002533	SA-1244	T-200227
NT1000333	SA-2244	T-210228
N11000333		I-Z1U
NT1000433, 244	SB308 128, 240	T-220228
•		
NT1000533	SB312 128. 240	T-221228
NT1000633, 244	SB320 128, 240	T-345228
NT1000833	SB330 128, 240	T-345K228
NT1001033	SB340 128, 240	T-346x228
NT1001233	SB351 128, 240	T-372 227
PC-48238	SB360 128, 240	T-373227
PD-15 231	SC308128. 240	T-374227
		1 -
PD-49 231, 232, 248	SC312 128, 240	T-375227
PD-75 231, 232, 248	SC320 128, 240	T-376227
PD-95231	SC330 128, 240	T-378227
	,	
PT2000433	SC340 128, 240	T-450-3
	,	
PT2004433	SC351 128, 240	T-460-2222
DTOOOS	,	I .
PT2000533	SC360 128, 240	T-560 230
PT2000633	SFK-8208	T-560-1230
PT2000833	SFK-12	T-560-2230
PT2001033	SFK-16 208	T-560-3 230
PT2001233	SFK-20	T-560-4230
PT2001633	SFK-24	T-560-5230
PT2300234	SFK-32	T-560-6230
PT2300334	SFK62-8 209	T-560-7 230
	SFK62-12209	
PT2300434		T-560-8 230
PT2300534	SFK62-16209	T-562
PT2300634	SFK62-20209	T-570222
PT2300834	SFK62-24 209	T-570-1222
PT2400434	SFK62-32 209	T-570-4222
PT2404434	SH-53230	T-570-6222
PT2400534	SJ308 128. 240	T-570-8222
	22340 120, 240	
		L

SC

T-570-16 222 TF5355X 172 12U 2 T-571-4 222 TF5356X 173 16U 2 T-571-6 222 TF5365X 174, 188 05703B-102 2 T-571-8 222 TF5375X 173 05704B-102 233, 2 T-571-16 222 TF5405X 175 05704B-104 233, 2 T-571-16 222 TF5405X 176 05704B-104 233, 2 T-1010 227 TF5425X 176 05705B-104 233, 2 T-102Z 228 TF5435X 176 05705B-104 233, 2 T-1037 226 TF5455X 177 05705B-002 233, 2 T-1037B 226 TF5506X 177 05705B-004 233, 2 T-1290 228 TF5516X 178 190 05705B-104 233, 2 T-1422R 225 228 TF5516X 178 190 05706B-161 233, 2 T-3710 227 </th <th></th> <th></th> <th></th>			
7.571-4 222 TF5358bx 173 ISU 2 7.571-8 222 TF5375x 173 6704B-102 23 7.571-8 222 TF540bx 175 6704B-102 233 7.571-16 222 TF540bx 176 6704B-102 233 7.571-16 222 TF540bx 176 6704B-102 233 7.1010 227 TF542bx 176 6706B-102 233 7.1022 228 TF543bx 176 6706B-102 233 7.1037H 226 TF545bx 177 9708B-104 233 2 7.1290 228 TF551bx 178 190 6706B-160 233 2 7.1292 228 TF551bx 179 190 6706B-160 233 2 7.1430 225 TF551bx 179 90706B-102 233 2 7.430 227 TF560bx 181 95706B-102 233 2	T-570-12 222	TF3959x147	10U249
T-571-6. 222 TF5398x. 174, 188 057038-102. 2 2 7-571-12. 233 2 7-571-12. 223 17-571-16. 222 17-5406x. 175 057048-104. 233 2 233 2 17-1010. 227 17-5406x. 178 057048-02. 233 2 233 17-1010. 227 17-5406x. 178 057048-04. 233 2 233 17-1010. 227 17-5408x. 176 057058-102. 233 2 17-1017. 233 2 17-1017. 233 2 17-1017. 233 2 17-1017. 233 2 17-1017. 233 2 17-1017. 233 2 2 17-1017. 233 2 2 17-1017. 233 2 233 2 2 17-1017. 230 2 2 2 2 2 233 2 2 2 2 2 2 2 3 2 2 2 3		TF5355x172	12U 249
7-571-8 222 TF5378x 173 057048-102 233 2 7-571-16 222 TF5406x 178 057048-02 233 2 7-571-16 222 TF5406x 178 057048-02 233 2 233 2 7-1022 228 175408x 176 057058-102 233 2 233 2 17571-18 228 175408x 176 057058-104 233 2 233 2 17571-18 238 2 233 2 17571-19 057058-104 233 2 233 2 17591-19 057058-104 233 2 233 2 17591-19 057058-104 233 2 233 2 17591-19 057058-104 233 2 233 2 17591-19 057058-104 233 2 233 2 257 175505x 181 057058-196 233 2 233 2 2 17591-19 057058-196 233 2 2 233 <td< th=""><th>T-571-4222</th><th>TF5356x 173</th><th>16U249</th></td<>	T-571-4 222	TF5356x 173	16U 249
T-57-1-12 222 TF-5408k .178 057048-02 .233 2 T-1010 227 TF-5408k .178 057058-102 .233 2 232 TF-5425k .176 057058-102 .233 2 237 174078 .266 175453k .176 057058-102 .233 2 .2710378 .266 175453k .177 057058-022 .233 .2710378 .266 175505k .174 057058-022 .233 .2710378 .268 .17590 .275058-022 .233 .2710378 .268 .17590 .275058-022 .233 .2710378 .2710 .2717 .27500 .2730 .2717 .27500 .27508-1561 .233 .2717 .2717 .2717 .2771 .27500 .27508-1561 .233 .2717 .2716 .2731 .2717 .2716 .2731 .2717 .2716 .2731 .2717 .2716 .2731 .2716 .2731 .2717 .2716 .2731 .2731 .2750		TF5365x 174, 188	05703B-102 233
T-57-1-16. 222 TF5408x .178 05704B-C02 .233 2 7.1022 .228 TF5425x .176 05705B-104 .233 2 323 2 7.1022 .228 TF5435x .176 05705B-104 .233 2 233 2 7.1037B .266 TF5560x .174 05705B-024 .233 2 7.1037H .266 TF5560x .177 05705B-064 .233 2 .233 2 7.1290 .288 175516x .179 190 05705B-1661 .233 .2 .17427B .288 .175516x .179 190 05705B-1661 .233 .2 .17422R .225 .225 .175516x .179 .179 .05705B-160 .233 .2 .17422R .225 .175516x .179 .05705B-160 .233 .2 .233 .174240 .27686-160 .233 .2 .174240 .27686-160 .233 .2 .174422R .27500 .2788 .178506 .283 .2	T-571-8 222	TF5375x 173	05704B-102 233, 249
T-1010	T-571-12 222	TF5405x175	05704B-104 233, 249
T-1022	T-571-16 222	TF5406x178	05704B-C02 233, 249
T-1037	T-1010227	TF5425x176	05705B-102 233, 249
T-1037B. 226 TF5505x	T-1022 228	TF5435x 176	05705B-104 233, 249
T-1037H		TF5455x177	05705B-C02 233, 249
7-1299 228 TF5515x .178, 190 05705B-1561 .233 2 233 2 T-1422R .252 289 TF5515x-L .179, 190 05706B-104 .233 2 233 2 T-1422R .252 528 TF5515x-L .179, 191 05706B-104 .233 2 233 2 T-14130 .271 TF5605x .181 05706B-106 .233 2 233 2 T-3716 .227 TF5605x .181 05706B-1060 .233 2 T-3716 .227 TF5605x .181 05706B-1060 .233 2 T-5000 .233 1 TF500x .179 05706B-1068 .233 2 T-5000 .223 TF5705x .179 05706B-1066 .233 2 T-5000 .233 1 TF500x .180 05706B-1066 .233 2 TF5000 .233 1 TF576x .181 .180 .05700B-1066 .13 .15 .15 .0500 .231 TF576x .181 .05710B-1066 .1 .1 .15 .15 .0500 .1 .15 .15 .0500 .1 .15 .15 .15 <th></th> <th>TF5505x174</th> <th>05705B-C04233, 249</th>		TF5505x174	05705B-C04233, 249
7-1295 229 TF6515vL		TF5506x 177	05705B-1560 233, 249
T-1422R 225 28 TF5615v-L 179 191 05708B-104 233 2 23 7 237 10 227 TF5625k 181 05708B-106 233 2 23 2 17-710 227 TF5625k 182 05708B-002 233 2 23 2 27-716 227 TF5665k 180 05708B-004 233 2 23 2 17-5002 223 TF5705k 179 05708B-004 233 2 25003 233 2 15003 223 TF5705k 180 05708B-1568 233 2 25000 233 2 15003 233 2 15006 233 1 15006		TF5515x178, 190	05705B-1561 233, 249
T-1430		TF5515x-L179, 190	05706B-102 233, 249
T-5710 227 TF5605x 181 05708B-02 233 2 233 2 233 2 233 2 233 2 233 2 233 2 233 2 3 2 233 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 1 5 50508 233 15606 233 15606 233 15606 233 15606 233 15606 233 15606 233 15606 233 15606 233 15606 233 15606 233 15605 181 3 36708 282 282 282 282 282 282 282 282 282 282 282 282		TF5515x-LL179, 191	05706B-104 233, 249
T-3712 227 TF5555x 182 D706B-C04 233 233 2 T5002 223 TF5706x 180 D5706B-1568 233 233 175003 223 TF5707x 182 D570B-1670 233 2 175004 223 TF5716x 183 D970B-108 1 1 15006 233 1 15716x 183 183 D9710B-108 1 1 15006 1 1 15006 1 1 15006 1 1 15006 1 1 15006 1 1 15006 1 1 1 15006 1 1 1 15006 1 1 15006 1 1 1 15006 1 1 1 15006 1		TF5525x 176	05706B-106 233, 249
T-5716 227 TF5708x 179 D5708B-1588 233 233 T-5003 223 TF5707x 182 D5708B-1570 233 233 T-5004 233 TF5707x 182 D5708B-1588 233 223 TF5706 182 D570B-108 1 1 7.5006 223 TF5716x 183 193 D570B-108 1 1 7.5006 223 TF5716x 181 193 D5710B-108 1 1 7.5008 223 TF5755x 180 D8710B-108 1 1 7.5010 223 TF5755x 180 D8710B-108 1 1 7.5012 2.201 1 7.5012 2.201 1 7.5012 2.201 1 7.5012 2.201 1 7.5012 2.201 1 7.5012 2.201 1 7.5012 2.201 1 7.5012 2.201 1 7.5012 2.201 2.201 2.201 2.201 2.201 2.201 2.201 2.201 2.201 <td< th=""><th></th><th>TF5605x181</th><th>05706B-C02233, 249</th></td<>		TF5605x 181	05706B-C02 233, 249
T-5002 223 TF5708 180 D5708B-1570 233 23 TF5707 182 D5710B-108 1 1 2570B-1570 182 D5710B-108 1 </th <th>-</th> <th></th> <th>05706B-C04233, 249</th>	-		05706B-C04 233, 249
T-5003 223 TF5707x 182 D5710B-108 1 T-5006 223 TF5716x 183 193 D5710B-108 1 T-5006 223 TF5716x 181 193 D5710B-066 1 T-5008 223 TF5726x 181 180 8712B-108 1 T-5010 223 TF5726x 181 80 8712B-108 1 T-5011 223 TF5758x 180 80 8X12PB 2 T-5016 223 TF5958x 180 80 8X12PB 2 T-5016 223 TF5958x 180 80 8X12PB 2 T-5016 223 TF5958x 180 80 8X12PB 2 T-5020 223 TH7010 222 8x25 208 209 2 T-5024 223 TH7010 222 8x25 208 209 2 T-5032 223 TH7014 222 8x65 22 T-5103 223 TH7014 222 8x65 22 T-5104 223 TH7020 222 8x65 22 <t< th=""><th></th><th>TF5705x 179</th><th>05706B-1568233, 249</th></t<>		TF5705x 179	05706B-1568 233, 249
T-5004. 223 TF5718x .183, 193 05710B-108. .1 T-5006. 223 TF5718x .181, 193 05710B-108. .1 T-5006. 223 TF5728x .181 05712B-108. .1 T-5010. 223 TF5755x .180 6X10 PB. .2 T-5012. 223 TF5955x .180 6X10 PB. .2 T-5012. 223 TF5955x .183 8251 .202. .2 T-5012. 223 TF5955x .183 8252 .208, 209, 2 .2 T-5012. 223 TF7010. .222 8252 .208, 209, 2 .2 T-5020. .23 TH7010. .222 8x663 .2			05706B-1570 233, 249
T-5006. 223 TF5778x 181,193 05710B-C06. 1 T-5008. 223 TF5728x 182 05712B-108. 1 T-5010. 223 TF5758x 180 6X10 PB. 2 T-5011. 223 TF5508x 180 8X12 PB. 2 T-5016. 223 TF5955x 183 8X251 20 T-5018. 223 TF7008. 222 8x252 208,209. T-5024. 223 TH7010. 222 8x254 208,29 T-5032. 223 TH7012. 222 8x853 2 T-5010. 223 TH7016. 222 8x853 2 T-5104. 223 TH7025. 222 12x251. 2 T-5106. 223 TH7025. 222 12x252. 208,209. T-5108. 223 TL708. 222 12x252. 208,209. T-5108. 223 TL703. 222 12x252. 208,209.			05710B-106 121
T-5006. 223 TF5726x 182 05712B-108 1 T-5018. 223 TF5726x 181 5K6 PB. 2 T-5010. 223 TF5755x 180 6X10 PB. 2 T-5012. 223 TF5955x 183 8X251 20 T-5016. 223 TF5955x 183 8X251 20 T-5020. 223 TH7010. 222 8x252 208, 209, 2 T-5032. 223 TH7014. 222 8x262 2 T-5103. 223 TH7014. 222 8x863 2 T-5104. 223 TH7020. 222 1x2251 2 T-5105. 223 TH7020. 222 1x2251 2 T-5106. 223 TH7020. 222 1x2251 2 T-5106. 223 TH7020. 222 1x2252 208, 209, 2 T-5108. 223 TL708. 222 1x2x54 208, 20			05710B-108 121
T-5008 223 TF5726x 181 SK6 PB 2 T-5010 223 TF5755x 180 6X10 PB 2 T-5012 223 TF5805x 180 8X12 PB 2 T-5016 223 TF5805x 183 8x251 2 T-5024 223 TH7008 222 8x252 208, 209, 2 T-5024 223 TH701 222 8x262 22 T-5012 223 TH701 222 8x562 22 T-5102 223 TH7016 222 8x863 2 T-5104 223 TH7016 222 8x863 2 T-5104 223 TH7025 222 12x254 208, 2 T-5106 223 TH7030 222 12x252 208, 209, 2 T-5116 223 TL7008 222 12x262 202, 2 T-5116 223 TL7011 222 12x624 208, 2 T-5116			05710B-C06 124
T-5010. 223 TF5755x 180 6X10 PB. 2 T-5012. 223 TF5805x. 180 8X12 PB. 2 T-5016. 223 TF5805x. 183 8x251. 22.0 T-5020. 223 TH7008. 222 8x252. 208, 209, 20 T-5024. 223 TH7010. 222 8x264. 208, 20 T-5032. 223 TH7014. 222 8x653. 22 T-5103. 223 TH7016. 222 8x663. 22 T-5104. 223 TH7020. 222 12x251. 22 T-5105. 223 TH7020. 222 12x252. 208, 209, 2 T-5106. 223 TH7020. 222 12x254. 208, 29 T-5108. 223 TH7020. 222 12x254. 208, 29 T-5108. 223 TL708. 222 12x262. 208, 29 T-5108. 223 TL708. 222 12x863. <t< th=""><th></th><th>TF5725x 182</th><th>05712B-108121</th></t<>		TF5725x 182	05712B-108 121
T-5012 223 TF5905x 180 8X12 PB 2 T-5016 223 TF5955x 83 8x251 2 T-5020 223 TH7008 222 8x252 208, 209, 2 T-5024 223 TH7010 222 8x262 22 T-5012 223 TH7011 222 8x662 2 T-5102 223 TH7016 222 8x863 2 T-5103 223 TH7016 222 8x863 2 T-5104 223 TH7025 222 12x251 2 T-5104 223 TH7025 222 12x252 208, 209, 2 T-5106 223 TH7030 222 12x252 208, 209, 2 T-5108 223 TH7019 222 12x254 208, 20 T-5110 223 TL7010 222 12x863 22 T-5110 223 TL7012 222 12x863 22 T-512		TF5726x181	5X6 PB 230
T-5016. 223 TF5955x 183 8x251. 2.2 2.5020. 223 TF5024. 2.23 TH7008. 2.22 8x252. 2.08.209.2 2.7 2.5024. 2.23 TH7010. 2.22 8x264. 2.08.209.2 2.7 2.5032. 2.23 TH7014. 2.22 8x263. 2.2 1.7 2.5103. 2.23 TH7014. 2.22 8x863. 2.2 1.7 2.5103. 2.23 TH7020. 2.22 1.2x261. 2.2 1.5104. 2.23 TH7020. 2.22 1.2x261. 2.2 1.5105. 2.23 TH7030. 2.22 1.2x262. 2.08.209.2 2.2 1.5106. 2.23 TH7030. 2.22 1.2x262. 2.08.209.2 2.5 1.5108. 2.22 1.5108. 2.22 1.5108. 2.22 1.5108. 2.22 1.5108. 2.22 1.5256. 2.08.209.2 2.5 2.5510. 2.08.209.2 2.5 2.5510. 2.08.209.2 2.5511. 2.22 1.5265. 2.08.209.2 2.5511. 2.22.			6X10 PB 230
T-5020 223 TH7008 222 8x252 208, 209, 2 27-5024 208, 209, 2 27-5024 208, 209, 2 27-5024 208, 209, 2 28x264 208, 20 208, 20 27-5024 208, 209, 2 27-5024 208, 209, 2 27-5024 208, 209, 2 22-2 8x262 208, 209, 2 27-5102 222 8x863 22 27-5104 223 TH7016 222 8x863 22 17-5104 223 TH7025 222 12x251 209, 20 22-2 12x256 209, 22 208, 209, 22 <th></th> <th>TF5805x 180</th> <th>8X12 PB 230</th>		TF5805x 180	8X12 PB 230
T-5024 223 TH7010 222 8x254 208, 22 T-5032 223 TH7012 222 8x262 22 T-5102 223 TH7014 222 8x863 22 T-5103 223 TH7020 222 12x251 22 T-5104 223 TH7020 222 12x251 22 T-5105 223 TH7025 222 12x252 208, 209, 2 T-5106 223 TH7030 222 12x252 208, 209, 2 T-5108 223 TH7030 222 12x252 208, 209, 2 T-5110 223 TL7010 222 12x863 2 T-5110 223 TL7012 222 12x863 2 T-5116 223 TL7014 222 12x863 2 T-5116 223 TL7015 222 16x251 2 2 T-5124 223 TL7018 222 16x254 208, 209, 2			8x251 208
T-5032 223 TH7014 222 8x262 2 T-5102 223 TH7014 222 8x853 2 T-5103 223 TH7016 222 8x863 2 T-5104 223 TH7020 222 12x251 2 2 T-5106 223 TH7025 222 12x252 20,8209, 2 2 T-5108 223 TL7008 222 12x254 208,209, 2 2 T-5108 223 TL7010 222 12x863 2 2 T-5110 223 TL7010 222 12x863 2 2 T-5112 223 TL7015 222 12x863 2 2 T-5120 223 TL7018 222 16x251 2		TH7008222	8x252 208, 209, 223
T-5102 223 TH7014 222 8x853 2 T-5103 223 TH7016 222 8x863 2 T-5104 223 TH7020 222 12x251 208 T-5105 223 TH7030 222 12x252 208 209 2 T-5108 223 TH7030 222 12x254 208 209 2 T-5108 223 TL7010 222 12x262 22 2 T-5110 223 TL7010 222 12x863 22 1 T-5116 223 TL7015 222 16x251 2 2 T-5124 223 TL7018 222 16x252 208 209 2 T-5124 223 TL7028 222 16x252 208 20 2 1 20 22 1 16x262 2 20 20 20 20 20 20 20 20 20		TH7010222	8x254 208, 209
T-5103 223 TH7016 222 1x251 22 1x251 22 22 22x251 22 22x251 22 22x251 22 22x251 22 22x252 208, 209, 22 22x252 208, 209, 22 22x254 208, 209, 22 22x354 208, 209, 22 22x364 208, 209, 22 22x364 208, 209, 22 22x36 20x1, 201, 201, 201 222 12x262 22 22x363 20x1, 201, 201, 201 222 12x363 20 22 12x363 20 22 12x363 20 22 12x364 208, 20 22 12x364 208, 20 22 12x364 208, 20 22 12x364 208, 20 22 12x364 20x264 208, 20 22 12x364 20x264 20x8, 20 22 12x364 20x8, 20<		TH7012222	8x262209
T-5104 223 TH7020 222 12x251 20 T-5105 223 TH7025 222 12x252 208, 209, 2 T-5108 223 TL7008 222 12x262 208, 209, 2 T-5110 223 TL7010 222 12x853 20 T-51112 223 TL7011 222 12x853 22 T-5116 223 TL7015 222 16x251 20 T-5116 223 TL7018 222 16x251 20 T-5120 223 TL7018 222 16x251 20 T-5124 223 TL7022 222 16x254 208, 209, 20 T-5124 223 TL7028 222 16x262 20 20 T-7003 222 TP16002 35 16x863 22 17003 222 TP16004 35 20x251 20 27 17003 222 TP16005 35 20x252 208, 209, 2 20x251		TH7014222	8x853 208
T-5106 223 TH7025 222 12x252 208, 209, 2 T-5106 223 TH7030 222 12x264 208, 2 T-5108 223 TL7008 222 12x662 22 T-5110 223 TL7010 222 12x863 22 T-5116 223 TL7015 222 16x851 22 T-5120 223 TL7018 222 16x252 208, 209, 2 T-5120 223 TL7018 222 16x252 208, 209, 2 T-5124 223 TL702 222 16x252 208, 209, 2 T-5125 223 TL702 222 16x252 208, 209, 2 T-5126 223 TL702 222 16x262 208, 209, 2 T-5127 222 TP16002 35 16x262 208, 209, 2 T-7003 222 TP16002 35 16x863 2 T-7004 222 TP16005 35 20x251 20		TH7016222	8x863 209
T-5106 223 TH7030 222 12x254 208, 20 T-5108 223 TL7008 222 12x862 22 T-5110 223 TL7010 222 12x863 22 T-5112 223 TL7012 222 12x863 22 T-5116 223 TL7015 222 16x251 22 T-5120 223 TL7018 222 16x252 208, 209, 2 T-5124 223 TL7022 222 16x254 208, 209, 2 T-5124 223 TL7022 222 16x252 208, 209, 2 T-5124 223 TL7022 222 16x254 208, 209, 2 T-5124 223 TL7022 222 16x262 22 2 T-7002 222 TP16002 35 16x853 2 2 T-7003 222 TP16005 35 16x863 2 2 T-7006 222 TP16006 35 2			12x251 208
T-5108 223 TL7008 222 12x262 22 T-5110 223 TL7010 222 12x853 22 T-5116 223 TL7015 222 12x863 22 T-5116 223 TL7015 222 16x251 208,209,22 T-5120 223 TL7018 222 16x252 208,209,22 T-5124 223 TL7022 222 16x252 208,209,22 T-5132 223 TL7028 222 16x262 208,209,22 T-7002 222 TP16002 35 16x863 20 T-7003 222 TP16002 35 16x863 22 T-7004 222 TP16004 35 20x251 22 T-7006 222 TP16005 35 20x252 208,209,2 T-7010 222 TP16008 35 20x252 208,209,2 T-7012 222 W05495 143 24x251 22		TH7025222	12x252 208, 209, 223
T-5110. 223 TL7010. 222 12x853. 20 T-5112. 223 TL7012. 222 12x863. 2 T-5116. 223 TL7015. 222 16x251. 22 T-5120. 223 TL7018. 222 16x252. 208, 209, 2 T-5124. 223 TL7028. 222 16x262. 208, 209, 2 T-5132. 223 TL7028. 222 16x262. 202 T-7002. 222 TP16002. 35 16x863. 2 T-7003. 222 TP16002. 35 16x863. 2 T-7004. 222 TP16005. 35 16x863. 2 T-7005. 222 TP16006. 35 20x251. 20 T-7010. 222 TP16008. 35 20x252. 208, 209, 2 T-7011. 222 W05498. 143, 243 20x853. 2 T-7014. 222 W05499. 143 24x251. 2			12x254 208, 209
T-5112 223 TL7012 222 12x863 22 T-5116 223 TL7015 222 16x251 22 T-5120 223 TL7018 222 16x252 208, 209, 22 T-5124 223 TL7022 222 16x262 22 T-5132 223 TL7028 222 16x262 22 T-7002 222 TP16002 35 16x853 2 T-7003 222 TP16004 35 16x863 2 T-7004 222 TP16005 35 20x251 2 T-7006 222 TP16006 35 20x252 208, 209, 2 T-7008 222 TP16008 35 20x254 20x254 T-7010 222 TP16008 35 20x254 20x820, 20 T-7014 222 W05465 143, 243 20x853 20x262 2 T-7014 222 W05499 143 24x254 20x29 </th <th></th> <th></th> <th>12x262209</th>			12x262 209
T-5116. 223 TL7015. 222 16x251. 20 27 20			
T-5120 223 TL7018 222 16x252 208, 209, 2 27. 5124 223 TL7022 222 16x254 208, 209, 2 22. 51532 208, 209, 2 22. 2 16x254 208, 209, 2 22. 2 17.002 222 17.008 222 17.009 35 16x853 20. 2 27. 7003 222 17.006 35 16x863 20x251 20x251 20x251 20x252 208, 209, 209, 209, 209, 209, 209, 209, 209			
T-5124 223 TL7022 222 16x254 208, 20 T-5132 223 TL7028 222 16x262 22 T-7002 222 TP16002 35 16x863 20 T-7003 222 TP16002 35 16x863 20 T-7004 222 TP16004 35 20x251 22 T-7005 222 TP16006 35 20x252 208, 209, 20 T-7008 222 TP16006 35 20x254 208, 20 20 T-7010 222 W05465 143, 243 20x853 20 20 T-7012 222 W05498 143 20x863 22 T-7014 222 W05499 143 24x251 20 T-7020 222 W1206 219 24x264 22 T-7024 222 W1206 219 24x264 22 T-7032 222 W15310 101, 118, 241, 243 24x863 22 TF-369x 144 W2032 101, 118, 241, 243 24x863			
T-5132 223 TL7028 222 16x262 22 T-7002 222 TP16002 35 16x853 2 T-7003 222 TP16004 35 20x251 22 T-7004 222 TP16004 35 20x251 20x T-7005 222 TP16005 35 20x252 208, 209, 27 T-7006 222 TP16008 35 20x254 208, 20 T-7010 222 W05465 143, 243 20x853 20 T-7012 222 W05498 143 20x863 22 T-7014 222 W05499 143 24x251 20 T-7020 222 W15730 143 24x252 208, 209, 27 T-7020 222 W1512 219 24x262 22 T-7024 222 W1512 219 24x262 22 TA-1004 224 W14630 219, 243 24x863 22			
T-7002 222 TP16002 35 16x853 21 T-7003 222 TP16025 35 16x863 21 T-7004 222 TP16005 35 20x251 22 T-7005 222 TP16005 35 20x252 208, 209, 22 T-7006 222 TP16006 35 20x254 208, 20 T-7010 222 TP16008 35 20x254 208, 20 T-7011 222 W05465 143, 243 20x853 22 T-7014 222 W05498 143 20x863 20 T-7014 222 W05499 143 24x251 22 T-7020 222 W1206 219 24x254 20 T-7024 222 W1212 219 24x262 22 T-7032 222 W1512 219 24x264 22 TA-1002 224, 248 W14630 219, 243 24x853 22 T			
T-7003. 222 TP16025. 35 16x863. 21 T-7004. 222 TP16004. 35 20x251. 22 T-7005. 222 TP16006. 35 20x252. 208, 209, 22 T-7006. 222 TP16006. 35 20x254. 208, 20 T-7010. 222 W05495. 143, 243 20x853. 21 T-7012. 222 W05498. 143 20x863. 20 T-7014. 222 W05499. 143 24x251. 22 T-7016. 222 W1206. 219 24x254. 20 T-7020. 222 W1206. 219 24x254. 22 T-7032. 222 W1512. 219 24x264. 22 TA-1002. 224, 248 W14630. 219, 243 24x863. 22 TF3359x. 143 W17709. 143 32x251. 208, 209, 22 TF3469x. 145, 192 W21204. 143 32x262.			
T-7004 222 TP16004 35 20x251 22 T-7005 222 TP16005 35 20x252 208, 209, 27 T-7006 222 TP16006 35 20x254 208, 20 T-7010 222 TP16008 35 20x262 20 T-7011 222 W05465 143, 243 20x853 20 T-7014 222 W05498 143 20x863 20 T-7016 222 W05499 143 24x251 20 T-7016 222 W05730 143 24x252 208, 209, 27 T-7020 222 W1206 219 24x254 20 T-7032 222 W1512 219 24x262 20 TA-1004 224 W1630 219, 243 24x863 22 TF3409x 143 W17709 143 32x251 20 TF3509x 144 W20332 101, 119 32x252 208, 209, 27 <			
T-7005 222 TP16005 35 20x252 208, 209, 20 T-7006 222 TP16006 35 20x254 208, 20 T-7008 222 TP16008 35 20x262 20 T-7010 222 W05465 143, 243 20x853 20 T-7014 222 W05498 143 20x863 21 T-7016 222 W05499 143 24x251 208, 209, 20 T-7016 222 W05730 143 24x252 208, 209, 20 T-7024 222 W1206 219 24x254 20 T-7032 222 W1212 219 24x262 22 TA-1002 224, 248 W14630 219, 243 24x863 20 TF3359x 143 W17709 143 32x251 208, 209, 20 TF3469x 145, 192 W21204 143 32x262 20 TF3559x 144 W23464 143 32x262 20 <th></th> <th></th> <th></th>			
T-7006 222 TP16006 35 20x254 208, 20 T-7008 222 TP16008 35 20x262 20 T-7010 222 W05465 143, 243 20x853 20 T-7012 222 W05498 143 24x251 22 T-7014 222 W05499 143 24x252 208, 209, 20 T-7020 222 W1206 219 24x254 20 T-7024 222 W1212 219 24x262 20 T-7032 222 W1512 219 24x264 20 TA-1002 224, 248 W14630 219, 243 24x863 21 TF3359x 143 W17709 143 32x251 20 TF3459x 144 W20332 101, 119 32x252 208, 209, 20 TF3509x 144 W23464 143 32x264 20 TF3569x 145, 189 W79850 219, 243 39x 20			
T-7008 222 TP16008 35 20x262 22 T-7010 222 W05465 143, 243 20x863 20 T-7014 222 W05498 143 24x251 22 T-7016 222 W05730 143 24x252 208, 209, 22 T-7020 222 W1206 219 24x254 20 T-7024 222 W1512 219 24x264 20 T-7032 222 W1512 219 24x264 20 TA-1002 224, 248 W14630 219, 243 24x853 20 TF3359x 143 W17709 143 32x251 20 TF3409x 144 W20332 101, 119 32x252 208, 209, 22 TF359x 145, 192 W21204 143 32x264 20 TF3559x 146 W76150 219, 243 32x863 20 TF3569x 145, 189 W79850 219, 243 39x 40x TF3609x 146 W8022 37, 42, 48, 104, 230 41x 43,			
T-7010. 222 W05465. 143, 243 20x853. 21 T-7012. 222 W05498. 143 20x863. 22 T-7014. 222 W05499. 143 24x251. 20x863. 21 T-7016. 222 W05730. 143 24x252. 208, 209, 27 22 T-7020. 222 W1206. 219 24x254. 22 208, 209, 27 22 T-7024. 222 W1212. 219 24x262. 22 21 T-7032. 222 W1512. 219 24x264. 22 22 TA-1002. 224, 248 W14630. 219, 243 24x863. 22 TF3359x. 143 W17709. 143 32x251. 20 TF3409x. 144 W20332. 101, 119 32x252. 208, 209, 22 TF359x. 144 W23464. 143 32x264. 20 TF3559x. 146 W76150. 219, 243 39x 2x TF3609x. 146 W8022. 37, 42, 48, 104, 230 41x 43			
T-7012 222 W05498 143 20x863 22 T-7014 222 W05499 143 24x251 208, 209, 27 T-7020 222 W1206 219 24x254 22 T-7024 222 W1212 219 24x262 22 T-7032 222 W1512 219 24x264 20 TA-1002 224, 248 W14630 219, 243 24x853 22 TF3359x 143 W17709 143 32x251 208, 209, 20 TF3409x 144 W20332 101, 119 32x252 208, 209, 20 TF359x 145, 192 W21204 143 32x262 20 TF3559x 146 W76150 219, 243 32x863 20 TF3569x 145, 189 W79850 219, 243 39x 145 TF3609x 146 W-8022 37, 42, 48, 104, 230 41x 43, 233, 22 TF3759x 146 O4U 249 42x 43x			
T-7014 222 W05499 143 24x251 21 T-7016 222 W05730 143 24x252 208, 209, 22 T-7020 222 W1206 219 24x264 20 T-7024 222 W1212 219 24x262 22 T-7032 222 W1512 219 24x264 20 TA-1002 224, 248 W14630 219, 243 24x863 20 TA-1004 224 W15310 101, 118, 241, 243 24x863 20 TF3359x 143 W17709 143 32x251 208, 209, 23 TF3469x 144 W20332 101, 119 32x252 208, 209, 23 TF3509x 144 W23464 143 32x264 20 TF3559x 146 W76150 219, 243 39x 20 TF3569x 145, 189 W79850 219, 243 39x 39x 37 TF3609x 146 W-8022 37, 42, 48, 104, 230 41x 43, 233, 23 TF3769x 146 04U 249 </th <th></th> <th></th> <th></th>			
T-7016. 222 W05730. 143 24x252. 208, 209, 20 T-7020. 222 W1206. 219 24x254. 20 T-7024. 222 W1212. 219 24x262. 20 T-7032. 222 W1512. 219 24x264. 20 TA-1002. 224, 248 W14630. 219, 243 24x853. 20 TA-1004. 224 W15310. 101, 118, 241, 243 24x863. 20 TF3359x. 143 W17709. 143 32x251. 208, 209, 20 TF3459x. 145, 192 W21204. 143 32x262. 208, 209, 20 TF3559x. 144 W23464. 143 32x262. 20 TF3559x. 146 W76150. 219, 243 39x 20 TF3569x. 145, 189 W79850. 219, 243 39x 20 TF3609x. 146 W-8022. 37, 42, 48, 104, 230 41x 43, 233, 23 TF3759x. 146 04U. 249 42x 43, 233, 23 TF3759x. 147 06U	-		
T-7020. 222 W1206. 219 24x254. 21 T-7024. 222 W1212. 219 24x262. 20 T-7032. 222 W1512. 219 24x264. 20 TA-1002. 224, 248 W14630. 219, 243 24x853. 20 TA-1004. 224 W15310. 101, 118, 241, 243 24x863. 20 TF3359x. 143 W17709. 143 32x251. 22 TF3409x. 144 W20332. 101, 119 32x252. 208, 209, 21 TF3509x. 144 W23464. 143 32x262. 20 TF3559x. 146 W76150. 219, 243 32x863. 20 TF3569x. 145, 189 W79850. 219, 243 39x 21 TF3609x. 146 W-8022. 37, 42, 48, 104, 230 41x 43, 233, 23 TF3759x. 146 04U. 249 42x 43, 23 TF3759x. 147 06U. 249 43x	-		
T-7024 222 W1212 219 24x262 21 T-7032 222 W1512 219 24x264 20 TA-1002 224, 248 W14630 219, 243 24x853 20 TA-1004 224 W15310 101, 118, 241, 243 24x863 20 TF3359x 143 W17709 143 32x251 208, 209, 21 TF3409x 144 W20332 101, 119 32x252 208, 209, 21 TF3509x 145, 192 W21204 143 32x262 20 TF3529x 146 W76150 219, 243 32x863 20 TF3559x 143 W79850 219, 243 39x 39x TF3609x 145, 189 W79851 219, 243 40x 43, 233, 25 TF3709x 146 W-8022 37, 42, 48, 104, 230 41x 43, 233, 25 TF3759x 147 06U 249 42x 43x			
T-7032 222 W1512 219 24x264 21 TA-1002 224, 248 W14630 219, 243 24x853 20 TA-1004 224 W15310 101, 118, 241, 243 24x863 20 TF3359x 143 W17709 143 32x251 208, 209, 27 TF3409x 144 W20332 101, 119 32x252 208, 209, 27 TF3509x 144 W23464 143 32x262 22 TF3529x 146 W76150 219, 243 32x863 20 TF3559x 143 W79850 219, 243 39x 20 TF3609x 145, 189 W79851 219, 243 40x 40x 20 TF3709x 146 W-8022 37, 42, 48, 104, 230 41x 43, 233, 23 TF3759x 147 06U 249 42x 43x			
TA-1002 224, 248 W14630 219, 243 24x853 20 TA-1004 224 W15310 101, 118, 241, 243 24x863 20 TF3359x 143 W17709 143 32x251 208, 209, 20 TF3469x 145, 192 W21204 143 32x262 208, 209, 20 TF3509x 144 W23464 143 32x264 20 TF3529x 146 W76150 219, 243 32x863 20 TF3569x 145, 189 W79850 219, 243 39x 20 TF3609x 146 W-8022 37, 42, 48, 104, 230 41x 43, 233, 23 TF3709x 146 04U 249 42x 43, 23 TF3759x 147 06U 249 43x 43x	-		
TA-1004 224 W15310 101, 118, 241, 243 24x863 20 TF3359x 143 W17709 143 32x251 208, 209, 23 TF3409x 144 W20332 101, 119 32x252 208, 209, 23 TF3509x 145, 192 W21204 143 32x262 22 TF3529x 146 W76150 219, 243 32x863 20 TF3559x 143 W79850 219, 243 39x 20 TF3609x 145, 189 W79851 219, 243 40x 20 TF3609x 146 W-8022 37, 42, 48, 104, 230 41x 43, 233, 23 TF3709x 146 04U 249 42x 43, 23 TF3759x 147 06U 249 43x 24x			
TF3359x 143 W17709 143 32x251 208, 209, 22 TF3409x 144 W20332 101, 119 32x252 208, 209, 22 TF3459x 145, 192 W21204 143 32x262 22 TF3509x 144 W23464 143 32x264 26 TF3559x 146 W76150 219, 243 32x863 26 TF3569x 145, 189 W79850 219, 243 39x 39x TF3609x 146 W-8022 37, 42, 48, 104, 230 41x 43, 233, 23 TF3709x 146 04U 249 42x 43, 23 TF3759x 147 06U 249 43x			
TF3409x 144 W20332 101, 119 32x252 208, 209, 22 TF3459x 145, 192 W21204 143 32x262 22 TF3509x 144 W23464 143 32x264 26 TF3559x 146 W76150 219, 243 32x863 26 TF3569x 145, 189 W79850 219, 243 39x 40x TF3609x 146 W-8022 37, 42, 48, 104, 230 41x 43, 233, 23 TF3709x 146 04U 249 42x 43, 23 TF3759x 147 06U 249 43x 43x			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
TF3459x 145, 192 W21204 143 32x262 2 TF3509x 144 W23464 143 32x264 2 TF3529x 146 W76150 219, 243 32x863 2 TF3559x 143 W79850 219, 243 39x 4 TF3669x 145, 189 W79851 219, 243 40x 40x 4 TF3609x 146 W-8022 37, 42, 48, 104, 230 41x 43, 233, 23 TF3709x 146 04U 249 42x 43, 23 TF3759x 147 06U 249 43x 43x			
TF3509x 144 W23464 143 32x264 2 TF3529x 146 W76150 219, 243 32x863 2 TF3559x 143 W79850 219, 243 39x 39x TF3669x 145, 189 W79851 219, 243 40x 40x 40x TF3609x 146 W-8022 37, 42, 48, 104, 230 41x 43, 233, 23 TF3709x 146 04U 249 42x 43, 23 TF3759x 147 06U 249 43x 43x		, , , , , ,	1 , , , , , , ,
TF3529x 146 W76150 219, 243 32x863 20 TF3559x 143 W79850 219, 243 39x 39x TF3569x 145, 189 W79851 219, 243 40x 40x TF3609x 146 W-8022 37, 42, 48, 104, 230 41x 43, 233, 23 TF3709x 146 04U 249 42x 43, 23 TF3759x 147 06U 249 43x 43x	· · · · · · · · · · · · · · · · · · ·		
TF3559x 143 W79850 219, 243 39x 47 TF3569x 145, 189 W79851 219, 243 40x			
TF3569x		· · · · · · · · · · · · · · · · · · ·	
TF3609x			
TF3709x			
TF3759x			1 '
			1
11 JUUJA			I -
	11 JUUJA 147	uou 249	44x4/

45x	47	252x	39, 233		6
	44		114, 233		7
	44, 233, 234		38, 128, 233, 234, 235, 236, 237		67, 23
	46, 233, 234		113		7
	46		113		69, 23
	47		113		7
	44		39		68, 23
	45		40, 233, 234, 235		7
	47		40		68, 23
	125		40	1	7
	49, 233, 234, 235		113	1	7
	49, 233, 234, 235		119		68, 23
	50, 233, 234, 235		56, 244		
	51		41		
	53, 233		56, 244		<u>6</u>
	52		57, 244		7
	51, 233		113		73
	50, 233, 234, 235		119		69, 23
	52, 233, 234, 235		57	1	
	52		59		74
	53		58		69, 23
	53		41	1	
	50, 51		57, 244	1	70
	53		57, 244		70, 23
	38, 233		58, 244		67, 23
1U5X	38, 111, 126, 233, 234,		113		
400	235, 236, 237		113		
			58		7
	117, 238		119		70
	117, 238 117, 238		41		7\ 7
	117, 238		119 115		7\ 7
	117, 238				7\ 7
	117, 238		59 59		6
	117, 238		56, 58		6
	117, 238	1	41	1	6
			50, 56		6
	117		80		6
	115		82		6
	117		81	1	6
	117		80		6
	117		81		6
	117		80		6
	117		81		6
	117		81		6
	117		82		6
	117		82	I	6
	114		80	I	62, 6
	38, 233, 234		126		101, 10
	114, 233, 234, 238		81		101, 10
	114, 233		82		101, 10
	4, 233, 234, 238, 241, 243		82		101, 10
	115		80	1344	101, 10
	50	1	80		101, 10
	51		- MM 217		101. 10
	53		PP 217	1351	101, 10
	52		66		98, 24
166x	51	1105x	·M 71		98, 24
168x	50	1107x	67		98, 24
	52		M 72	1364x	10
170x	52	1108P	x 77	1365x	99
171x	53	1108x	.S 68	1366x	99
172x	53	1108x	. M72	1368x	98, 24
174x	51	1109x	66	1369x	99, 24
176x	53	1109x	· M 71		9
	114		43	1	10
	114		66		10
	39, 233, 234, 235		MRP 71	1372x	10
230	114	1150x	PP 216	1380x	99
		l .			

SC

1382x	100	1563	39, 45, 123	1914	137
	121	1564x	134	1915	137
	121		134		137
	116	1	134	1	137
	116		134		137
	116		132		137
	116	1	132	1	137
	116	1	131		137
	A 116		131		137
	116	1	133		137
	116	1	133	1	137
	115	1	133		137
	115		133		137
	115	1	135		137
	116		135	1	137
	121		134		137
	121		134		137
	121	1	131	1	137
	116	1	131	1	137
	122		135		137
	122		135		137
	122	1	123		137
	126		123		137
	127, 233	1	50, 56		137
	127, 233		57		137
	122		57	1	137
	122		59		137
	122		58		137
	122		57		137
	116		57	1	137
	92, 241, 241, 244		58 58		137
	92, 241, 241, 244 92, 241, 241, 244				49, 56, 233
	92, 241, 241, 244	1	59		49, 50, 233 142
	· · · · · · · · · · · · · · · · · · ·		59	1	
	94 93, 241, 244	1	58 90, 242	1 '	141 105, 233
	93, 241, 244		90, 242		105, 233 105, 233, 234
	93, 241, 241, 244	1	90, 242		105, 233, 234, 235 105, 233, 234, 235
	94, 241, 241, 244	1	90		105, 233, 234, 236
	94		85		105, 255, 254, 256
	95, 241		85, 242		140
	95, 241, 244		88	1	105, 233, 234
1474x	93		87		106, 233, 234, 235, 236
	95		86		141
	93, 241		86, 242	1	106
	96	1	87, 242		106. 233. 234. 235. 236
	96. 241. 241. 244	1	87		142
	96, 244		88	3325x	107, 233, 234
	136	1	88		107, 233, 234, 236
1502Px	136		89		107, 233, 234
1512	106, 122	1871x-S	89		107, 233, 234
	123, 125	1	89		107
	40, 106, 123, 233		90		107
	39, 45, 123	1	85		107
1521	45, 123	1874x	85, 242		108, 233, 234, 236
	39, 45, 123	1877x	90	3371x	143
1529x	136	1880x	86, 242	3400x	108, 233, 234, 236
	136	1880x-S	87	3421x	144
	136		90		109, 233, 236
	233		137		144
	233		137		146
	233	1	137		109, 233
	221, 233		137		146
	39, 45, 123		137	1	109, 233, 234
	39, 45, 123		137		146
	135	1	137		109, 233, 235
	135		137		147
	132	1	137	1	109
1562Px	132	1913	137	4105x	157
		I .		1	

4129x	157	6206.004	245	7504	117
4165x					
4165X	157		245	1	204
4205x 142,			103		117
4213x 159,			103	1	117
4229x	158	6600	116	7509	117
4305x	158	6660	115, 233	7515x	192, 205
4307x	199	6700	113	7517x	204
4315x 158,			113	1	205
4316x 159,			120	1	206
4325x			120	1	206
4355x			120		47, 171, 183, 194, 207, 223
4365 x160,			112		206
4375x			118		206
4405x	161	6724	118	7709	127
4505x	160	6729	118	7705x	205
4515x	161	6737	120	7715x	194. 207
4525x			120	7716x	193, 206
4535x 162.			120	1	205
4629x 138, 163,			120	1	
				1	126, 194
4640x			120, 233	1	207
4705x			115	1	206
4715x 162, 191,	194	6788	114	7732	126
4716x 163,	194	6800	112	7755x	205
4726x			120		127
4924x			112		205
				1	
4955x			120, 233	1	126
5027x			112		127
5117x			112		205
5141x	167	6820	112	7812	127
5177x	166	6824	119	7817	126
5188	127	6825	112	7818	126, 233, 236
5217x			120		126, 233, 236
5241x			119, 233		126, 233, 236
5267x			118		38, 126. 233. 235, 236, 237
5317x			118, 233		126, 236
5318x			118	7898	127, 236, 237
5327x 170,	187	7015x	202	7900	127, 236, 237
5337x	168	7027x	202	7901	127, 236, 237
5367x		7033x	184		127, 233, 236, 237
5368x			201		127, 236, 237
5417x			201		127, 233, 236, 237
5467x			202	1	126, 233, 236
5517x			202	1	126
5518x			201	7910	126, 236
5527x 178,	190	7165x-MM	211, 248, 249	7911	126, 236
5537x	176	7176x	201	7912	126, 236
5617x		7205x	203	7913	126, 236
5667x			203		127, 233, 236, 237
5717x			202		125, 126
5717X5718x			184		125, 126
				1	· · · · · · · · · · · · · · · · · · ·
5719x			184		126, 236
5737x			202	1	237
5767x	180		203		201
5967x	183	7267x	203	7933	127, 236, 237
6100x 103, 125,	233	7305x	202	7934A	128, 233, 237
6200x 103,		7306x	202		127, 233, 237
6202			186, 203		127, 233, 237
6203-010			202		167, 201
6203-016			202		127, 233, 237
6203-020			203		128, 233, 237
6203-024			186, 203	7941	128, 233, 237
6203-036	245	7337x	203	7955x	207
6204-010			204	1	207
6204-016			204	1	127, 237
6204-020			204	1	237
				1	
6204-024			204		237
6204-036			204		127, 237
6205-004		7467x	204	7977	124
6205-006	245	7502	117	7978	124

Index

8112x	
8165x	201
8367	
8370	220, 221
8371	220, 221
8372	220. 221
8373	220. 221
8374	220 221
8375	221
8376	221
8377	221
8378	221
9100x	1/0 171
9151x	140, 171 46 452
9154x	40, 132
9205x	45, 150
9205X	148
9255x	149
9315x	149, 186
9355x	150
9365x	151, 189
9385x	150
9405x	151
9405x-LL	151
9406x	153
9435x	153
9455x	152
9456x	153
9515x	152, 153
9705x	219
10004B-102	246
10004B-104	246
10004B-304	246
10004B-305	246
10004B-405	246
10004B-604	246
10004B-A04	246
10004B-A05	246
10004B-B03	246
10004B-B04	246
10004B-B04 10004B-B05	246 246
10004B-B05	246
10004B-B05 10004B-Y04	246 246
10004B-B05 10004B-Y04 10005B-102	246 246 246
10004B-B05 10004B-Y04 10005B-102 10005B-104	246 246 246
10004B-B05 10004B-Y04 10005B-102 10005B-104 10005B-405	246 246 246 246
10004B-B05 10004B-Y04 10005B-102 10005B-104 10005B-405	246 246 246 246 246
10004B-B05 10004B-Y04 10005B-102 10005B-104 10005B-405 10005B-B05	
10004B-B05	

24706N-606	
24706N-608	247
24706N-756	247
24706N-B06	24
24708N-106	
24808N-108	
24808N-406	
24808N-60824710B-Y58	247
24710B-Y60 24710N-108	
24710N-608	
24710N-610	247
33806-A	243 247
33806-B	
33806B-Y06	243 247
33806B-Y24	243 247
33806B-Y26	243 247
33806B-Y28	243 247
33806B-Y34	243. 247
33806B-Y36	247
33806B-Y38	243. 247
38166-01812	245
38166-02137	245
38166-02412	245
38166-02837	
38166-03012	
38166-03200	245
38166-03437	245
38166-03612	
38166-04112	
38353-01800	245
38353-02037	
38353-02400	245
38353-02837	
38353-03000	245
38353-03200	
38353-03437	
38353-03600	
38353-0411241157x	240 124 174
50008	124, 17 209
50008x12	208
50012	
50016	208
50016x20	208
50020x16	
50020	
50024	208
50032	
54508	208
54508x12	208
54512	
54516	
54516x20	
54520x16	
54520	
54524	
54532	
59008	
59008x12	
59012	
59016	
59016x2059020x16	
59020x16	
59024	
59032	
60008	200 2∩0

60012	209
60016	209
60020	209
60024	
60032	209
64508	
64512	209
64516	
64520	
64524	
64532	
69008	
69012	
69016	
69020	
69024	
69032	
106370	
106470	221
211273A	
211280A	
£11200A	110

Notes	Notes

Notes	Notes
•	

Notes	Notes

Notes	Notes

Notes	Notes

Notes	Notes

	Notes	Notes
_		
_		
_		