

Equipment

Coll-O-Crimp T-407



Refer to safety information regarding Coll-O-Crimp hose, hose fittings and assembly equipment compatibility on page 3.

T-407-1 • Production Coll-O-Crimp Press



*Removal of crimp locator allows for crimping of 45° and 90° angle hose end configurations.

Refer to pages 356-367 for Coll-O-Crimp tooling, tooling packages and pumps.

Refer to safety information regarding Coll-O-Crimp crimping procedures on page 345.

The T-407-1 Production Coll-O-Crimp, as its name implies, is at its best in the fast production of *straight configuration hose end crimping. Taking advantage of the swiveling bracket which supports the crimper, tooling can be put in place and the press locked in at up to a 90° angle, facilitating quick hose end crimping. A crimp locator is included. When set to position, the crimp locator allows for a preset of the correct crimp location so hose assemblies can be built in volume, with accuracy and precision. The T-407-1 offers crimping capabilities of 3/16"-1 fiber braid through 1-3/8" I.D. 1 wire hose and 1-1/4" I.D. 2 wire hose.

Weight: (for press and pump) 198 lbs.

Size Press: 16-1/4" high, 21-3/4" deep

Includes one each of the following:

CATALOG NUMBER	DESCRIPTION
T-400-M	Instructions
T-400-8	Die Ring
T-400-9	Crimp Locator
T-400-19	60" hose assembly and fittings

T-407 • Production Coll-O-Crimp Package

The T-407 comes with a high volume pump and a foot switch.

Size Pump: 26" high, 18" wide
(Pump is wired for 220v, 1 phase)

Includes one each of the following:

CATALOG NUMBER	DESCRIPTION
T-407-1	Production C-O-C Press
T-433	Two-Stage Piston Pump and foot switch

Note: The T-433 pump which is shipped as part of the T-407 Production Coll-O-Crimp System.

T-433-1 • Foot Switch



Lightweight and easy to use, the T-433-1 is designed with the operator in mind. Colored safety orange, the T-433-1 electric foot switch allows for hands free operation.

For use with T-407-1 C-O-C Production System.