


# Polycoil® Brass Hose Products

## H130 Coiled Hose Polycoil® Hose



- Hose Construction: Nylon 12 extruded.
- Color: Yellow
- Temperature: -40°F to +200°F (-40°C to +93°C)
- Application: All types of air tools.
- Working Length: For 100' of Polycoil® is 94'.
- Easy to clean.
- Self-retracting.
- Lightweight.
- Easy to handle.
- Out of the way when not in use.
- Eliminates need for reels and other expensive take-up devices.
- May also be ordered as ready-made hose assemblies. See below.

HOSE I.D.	HOSE O.D.	CATALOG NUMBER	RECOM. OPER. PRESS. 76°F	MIN. BURST PRESSURE	RETRACTED LENGTH	*STD. PACK
1/4	.316	H13004-100	200	800	39-1/4	1200'
3/8	.465	H13006-100	200	800	34-1/2	600'


\*Packaged in 100' continuous lengths.

Higher temperatures reduce pressure capabilities and retractability.

**⚠ Caution:** Product should not be used in applications where temperature exceeds 200° F. Exceeding temperature level could result in hose rupture.

# Polycoil® Brass Hose Products

## Polycoil® Assemblies




NOMINAL HOSE I.D.	MAXIMUM WORKING LENGTH	MALE PIPE RIGID	MALE PIPE SWIVEL	CATALOG NUMBER	NOMINAL COIL O.D.
1/4"	10.5'	–	1/4"	13004JJ-12†	3-1/2"
1/4"	10.5'	1/4"	1/4"	130041J-12	3-1/2"
1/4"	10.5'	1/4"	–	1300411-12*	3-1/2"
1/4"	23.5'	–	1/4"	13004JJ-25†	3-1/2"
1/4"	23.5'	1/4"	1/4"	130041J-25	3-1/2"
1/4"	23.5'	1/4"	–	1300411-25*	3-1/2"
1/4"	47'	–	1/4"	13004JJ-50†	3-1/2"
1/4"	47'	1/4"	1/4"	130041J-50	3-1/2"
1/4"	47'	1/4"	–	1300411-50*	3-1/2"
3/8"	10.5'	–	3/8"	13006JJ-12†	5-3/4"
3/8"	10.5'	3/8"	3/8"	130061J-12	5-3/4"
3/8"	10.5'	3/8"	–	1300611-12*	5-3/4"
3/8"	23.5'	–	3/8"	13006JJ-25†	5-3/4"
3/8"	23.5'	3/8"	3/8"	130061J-25	5-3/4"
3/8"	23.5'	3/8"	–	1300611-25*	5-3/4"
3/8"	47'	–	3/8"	13006JJ-50†	5-3/4"
3/8"	47'	3/8"	3/8"	130061J-50	5-3/4"
3/8"	47'	3/8"	–	1300611-50*	5-3/4"

†Male pipe swivel on both ends.

\*Male pipe rigid on both ends.

# Polycoil® Brass Hose Products

## 13000 Series Brass Hose Ends




**Typical Application:** Shop air with pneumatic air tools.

**Material:** CA360 Brass.

**Used With:** H130 Hose.


**Advantages:** Self-storing, compact and low cost.

 **Caution:** Overtightening may be detrimental to the connection.

## Polycoil® Assembly Instructions


1. Assemble onto hose in this order:
  - a. Spring guard
  - b. Nut and sleeve
  - c. End fitting—make sure hose is bottomed
2. Tighten nut and sleeve onto fitting—finger tight
3. Tighten nut onto fitting 1-1/2 additional turns
4. Assemble spring guard over nut

## Sleeve (Plastic)



HOSE I.D.	CATALOG NUMBER
1/4	13004-A
3/8	13006-A

## Nut (Brass)



HOSE I.D.	CATALOG NUMBER
1/4	13004-B
3/8	13006-B


# Polycoil® Brass Hose Products

**Spring Guard  
(Steel)**




HOSE I.D.	CATALOG NUMBER
1/4	13004-C
3/8	13006-C

**Male Pipe Rigid  
(Brass)**



HOSE I.D.	MALE PIPE SIZE	CATALOG NUMBER
1/4	1/4	13004-1
3/8	3/8	13006-1

**Male Pipe Swivel  
(Brass)**



HOSE I.D.	MALE PIPE SIZE	CATALOG NUMBER
1/4	1/4	13004-J
3/8	3/8	13006-J